

Mark Scheme (Results)

January 2022

Pearson Edexcel International A Level In Mechanics M2 (WME02) Paper 01

1a	Use of $\mathbf{I} = m\mathbf{v} - m\mathbf{u}$	M1	Condone subtraction in the wrong order.
	$ \binom{-4}{6} = \frac{1}{2} \binom{x-2}{y-4} $	A1	Correct unsimplified equation Any equivalent form. Allow with v
	$\mathbf{v} = -6\mathbf{i} + 16\mathbf{j} \left( \mathbf{m}  \mathbf{s}^{-1} \right)$	A1	Correct only. Seen or implied SR: Allow 3/3 if stop at $\mathbf{v} = 6\mathbf{i} - 16\mathbf{j} \left( \mathbf{m}  \mathbf{s}^{-1} \right)$
	$\left \mathbf{v}\right  = \sqrt{\left(-6\right)^2 + 16^2}$	M1	Correct use of Pythagoras with their v
	$=\sqrt{292}\left(=2\sqrt{73}\right)\left(\mathrm{ms^{-1}}\right)$	A1	Correct simplified value. 17 or better (17.088) Allow 5/5 if working from the negative
		[5]	of the velocity.
1b	Correct use of trigonometry to find 2 relevant angles - as values or in inverse tangent form	M1	For their v e.g. $\pm 69.44^{\circ}, 63.43^{\circ}$ or $\pm 1.212, 0.4636$
	$\theta = \left(180^{\circ} - \tan^{-1}\frac{16}{6}\right) - \tan^{-1}\frac{4}{2}$	A1ft	Correct unsimplified expression for $\theta$ Any equivalent form
	= 47°	A1	47° or better (47.121) 312.9° Accept radians (0.8224)
		[3]	
1b alt	Use of scalar product with two relevant vectors	M1	For their <b>v</b>
	$\theta = \cos^{-1}\left(\frac{-12 + 64}{\sqrt{20}\sqrt{292}}\right)$	A1ft	Correct unsimplified expression for $\cos \theta$ or equivalent
	= 47°	A1	47° or better (47.121) 312.9° Accept radians (0.8224)
		[3] (8)	
		(0)	

		3.61	N 1 11 / D' ' 11
2.a	Equation of motion for car and trailer	M1	Need all terms. Dimensionally correct.
			Condone sin/cos confusion and sign
			errors.
	$E_{200-150} = 200g = 600g = 0$	A1	Unsimplified equation in $P$ or $F$ with at
	$F - 300 - 130 - {20} - {20} = 0$		most one error
	$F - 300 - 150 - \frac{200g}{20} - \frac{600g}{20} = 0$ $(F - 842 = 0)$	A1	Correct unsimplified equation in <i>P</i> or <i>F</i>
	(F-642=0)		Missing g is one accuracy error
			Ç
	1000P ( 450 08 204 0)	M1	Use of $P = Fv$
	$\frac{1000P}{15} \left( -450 - 98 - 294 = 0 \right)$ $P = 12.6 \text{ or } P = 13$		Allow with <i>P</i> or 1000 <i>P</i>
	P = 12.6  or  P = 13	A1	3 s.f. or 2 s.f. only
			A final answer of 12600 (13000) scores
			4/5
			Condone 12600=12.6 (correct thinking
			without stating the units)
		[5]	
2b	KE lost = gain in GPE + WD against	M1	Must be using work-energy principle
	resistance		for trailer only. Dimensionally correct.
			Correct terms and no extras. Condone
			sign errors and sin / cos confusion.
	1 200	A1	Correct unsimplified equation in one
	$\frac{1}{2} \times 200 \times 400 = \frac{200}{20} gd + 300d (= 398d)$		variable with at most one error
	20	A1	Correct unsimplified equation in one
			variable.
	XY = d = 101 (100)  (m)	A1	3 s.f. or 2 s.f. only
		[4]	
		(9)	

3a	Use of $\mathbf{a} = \frac{d\mathbf{v}}{dt}$ $(\mathbf{a} = 18\cos 3t \mathbf{i} - 2\sin t \mathbf{j})$	M1	Differentiate to obtain $\mathbf{a} = \lambda \cos 3t  \mathbf{i} + \mu \sin t  \mathbf{j}$
	Use of $\mathbf{F} = m\mathbf{a} : \mathbf{F} = \frac{1}{4}\mathbf{a}$	M1	Must be working in vectors
	$\mathbf{F} = \frac{9}{2}\cos 3t\mathbf{i} - \frac{1}{2}\sin t\mathbf{j}$	A1	Or equivalent. e.g. as a column vector
		[3]	
3b	$2\cos t + 1 = 0$	M1	Set <b>j</b> component of $\mathbf{v} = 0$ and solve for $t$
	$\Rightarrow t = \frac{2\pi}{3}$	A1	ISW if correct answer seen. Only answer 120° scores A0 here and the final A0
	Use of $\mathbf{v} = \frac{d\mathbf{r}}{dt}$ $(\mathbf{r} = -2\cos 3t \mathbf{i} + (t + 2\sin t) \mathbf{j}(+\mathbf{C}))$	M1	Integrate <b>v</b> with respect to <i>t</i> to obtain $\mathbf{r} = p \cos 3t \mathbf{i} + (t + q \sin t) \mathbf{j}(+\mathbf{C})$ Condone if there is no constant of integration.
	$t = 0,  \mathbf{r} = (4\mathbf{i} - \sqrt{3}\mathbf{j})\mathbf{m}$ $\mathbf{r} = (-2\cos 3t + 6)\mathbf{i} + (t + 2\sin t - \sqrt{3})\mathbf{j}$	M1	Correct use of boundary condition to find their <b>C</b> . Could be part of a definite integral e.g. $4\mathbf{i} - \sqrt{3}\mathbf{j} + \int_0^t 6\sin 3t\mathbf{i} + (1 + 2\cos t)\mathbf{j}dt$ for their upper limit
	$=4\mathbf{i}+\frac{2\pi}{3}\mathbf{j} (m)$	A1 A1	Accept 4 <b>i</b> + 2.1 <b>j</b> or better one component correct both components correct  ISW if they also offer 4 <b>i</b> + 120 <b>j</b> "correct" components after an M0 are fortuitous – A0
		[6]	
		(9)	

4a	2 <i>u</i> —				
	$A \atop 2m$	B 3	3m		
	ν <		$\xrightarrow{w}$		
	Use of CLM	M1	Need all terms, dimensionally correct. Condone sign errors.		
	4mu - 3mu = 3mw - 2mv $(u = 3w - 2v)$	A1	Correct unsimplified equation		
	Use of impact law	M1	Used correctly. Condone sign errors		
	v + w = 3eu	A1	Correct unsimplified equation. Signs consistent with their CLM equation		
	$\begin{cases} u = 3w - 2v \\ 6eu = 2w + 2v \end{cases}$	DM1	Dependent on both preceding M marks. Solve to find speed of <i>B</i> .		
	$\Rightarrow 5w = u + 6eu,  w = \frac{1}{5}u(1 + 6e)  *$	A1*	Obtain <b>given answer</b> from correct working		
		[6]			
4b	$v = 3eu - w = \frac{u}{5}(9e - 1)$	B1	Check their diagram / directions and allow $v = \frac{u}{5}(1-9e)$ if correct for their working.  Any equivalent form.  Must be seen or used in (b)		
	$x = \frac{u}{7}(1 + 6e)$	B1	Seen or implied. Accept ±		
	Second collision if $\frac{u}{7}(1+6e) > \frac{u}{5}(9e-1)$	M1	Correct inequality to find the upper limit for <i>e</i> , using their <i>v</i> and <i>x</i>		
	$(0<)e<\frac{4}{11}$	A1	Final answer. Or equivalent Do not need to mention the lower limit, but if they do it must be stated correctly (strict inequality).		
		[4]			

5a	k₩ ^ B		
	C 4a C		
	A $B$		
	Angle ACO is a right angle or	B1*	Or equivalent explanation of given
	State that $AB$ is a tangent hence triangle is $5a$ ,	DI.	Or equivalent <b>explanation</b> of <b>given answer.</b> They need to say why it is a 5,
	12 <i>a</i> , <u>13<i>a</i> *</u>		12, 13 triangle. If they say nothing,
			check the diagram to see if there is a
		[1]	right angle marked.
		L¹J	
5b	Moments about A:	M1	Dimensionally correct equation Condone sin / cos confusion
	$W \times 8a \cos \alpha = kW \times 12a$		
	$\left(W \times 8a \times \frac{12}{13} = kW \times 12a\right)$ $k = \frac{8}{13} *$	A1	Correct unsimplified equation
	k = 8 *		Obtain given answer from correct
	13	A1*	working. Need to see correct substitution for $\cos \alpha$ and correct final
			substitution for $\cos \alpha$ and correct final statement.
		[3]	
5c	$\leftrightarrow R_{H} = kW \sin \alpha$	M1	First equation e.g. resolve horizontally. Condone sin/cos confusion
	$=\frac{8W}{13}\times\frac{5}{13}=\frac{40W}{169}$	A1	Correct unsimplified expression for $R_H$
	$\updownarrow R_{V} + kW \cos \alpha = W$	M1	Second equation e.g. resolve vertically. Condone sin/cos confusion and sign errors.
	$R_V = W - \frac{8W}{13} \times \frac{12}{13} = \frac{73W}{169}$	A1	Correct unsimplified expression for $R_V$
	$\left R\right ^2 = \left(R_V\right)^2 + \left(R_H\right)^2$	DM1	Dependent on the two preceding M marks. Method to obtain the magnitude, e.g. correct use of Pythagoras
	$ R  = \frac{W}{169} \sqrt{40^2 + 73^2}$		Accept 0.49W or better
	$= \frac{\sqrt{6929}}{169}W = \frac{\sqrt{41}}{13}W$	A1	Allow $\sqrt{\frac{41W^2}{169}}$ or correct unsimplified
	169 13		form. ISW
	$\tan \theta^{\circ} = \frac{73}{40}  (=1.825)$	DM1	Dependent on the first 2 M marks. Method to obtain the angle, e.g. correct use of trigonometry to find a relevant angle $(\theta \text{ or } 90 - \theta)$
	$\theta = 61  (61.3)$	A1	61 or better (61.2796)
	· · · · · · · · · · · · · · · · · · ·	[8]	
<i>5</i> .	See overleaf for alternatives		Plant and the state of
5c Alt	$P = W \sin \alpha$	M1	First equation e.g. resolve parallel to the rod. Condone sin/cos confusion.
	<u>L</u>	1	

	5W		Correct unsimplified expression for
	$=\frac{5W}{13}$	A1	parallel component
	$Q + kW = W \cos \alpha$	M1	Second equation e.g. resolve perpendicular to the rod. Condone sin/cos confusion and sign errors.
	$Q = \frac{12}{13}W - \frac{8}{13}W = \frac{4W}{13}$ $ R  = \sqrt{P^2 + Q^2}$	A1	Correct unsimplified expression for perpendicular component
	$ R  = \sqrt{P^2 + Q^2}$	DM1	Dependent on the first 2 M marks. Correct use of Pythagoras
	$ R  = \frac{W}{13} \sqrt{4^2 + 5^2} = \frac{\sqrt{41}}{13} W$ $\theta^{\circ} = \tan^{-1} \frac{5}{12} + \tan^{-1} \frac{4}{5}$	A1	Accept 0.49W or better Allow correct unsimplified form
	$\theta^{\circ} = \tan^{-1} \frac{5}{12} + \tan^{-1} \frac{4}{5}$	DM1	Dependent on the first 2 M marks.  Correct use of trig to find the required angle
	$\theta = 61  (61.3)$	A1	61 or better (61.2796)
		[8]	
5c Alt2	$R - \beta$ $W$ $a$	M1 A1	Vector diagram showing the three forces acting Correctly configured
	Use of Cosine Rule:	M1	Correct use of cosine rule for their triangle
	$R^2 = W^2 + (kW)^2 - 2W(kW)\cos\alpha$	A1	Correct unsimplified equation.
	$R^{2} = W^{2} + \frac{64}{169}W^{2} - \frac{16}{13} \times \frac{12}{13}W^{2} \left( = \frac{41}{169}W^{2} \right)$	DM1	Solve for <i>R</i> . Dependent on the first 2 M marks
	$ R  = \frac{\sqrt{41}}{13}W$	A1	Accept 0.49W or better
	$\frac{R}{\sin \alpha} = \frac{kW}{\sin \beta}  \left( \sin \beta = \frac{8}{13} \times \frac{\sqrt{41}}{13} \times \frac{5}{13} \right)$	DM1	Dependent on the first M mark. Correct method to find a relevant angle e.g. by use of sine rule
	$\theta = 90 - 28.7 = 61.3$	A1 [8]	61 or better (61.2796)
	<u> </u>		
		(12)	
<u> </u>		l .	

6a	Mass ratio		
	$24a:25a:7\pi a:7a(7+\pi)$	B1	Correct ratio seen or implied
	Moments about AE	M1	Need all terms, with their masses and horizontal distances Allow use of a parallel axis.
	$25a \times \frac{7}{2}a + 7\pi a \times \frac{14a}{\pi}$ $= 7a(7+\pi)d$	A1	Correct unsimplified equation
	$\frac{371}{2}a^2 = 7a(7+\pi)d$ $\Rightarrow d = \frac{53}{2(7+\pi)}a \qquad *$	A1*	Obtain <b>given answer</b> from correct working Condone if they call it $\overline{x}$
6b	Centre of mass of semicircle lies 7 <i>a</i> "vertically below" <i>A</i>	B1	Seen or implied e.g. 17a above E
	Moments about "horizontal" axis through A:	M1	Or a parallel axis. Need all terms, with their masses and distances.
	$24a \times 12a + 25a \times 12a + 7\pi a \times 7a$ $= 7a(7+\pi)y$	A1	Correct unsimplified equation
	$y = \frac{49a(12+\pi)}{7(7+\pi)} \left( = \frac{7a(12+\pi)}{7+\pi} \right)$	A1	Any equivalent form.  Accept $\frac{84+17\pi}{7+\pi}a$ from $E$
	NB: A candidate might have a vector equation in or the first 4 marks in (b).	(a) whicl	
	$\frac{1}{d}$		
	$\theta^{\circ} = \tan^{-1} \frac{d}{y} = \tan^{-1} \frac{53}{14(12+\pi)} (=14.037^{\circ})$	DM1	Use trig to find relevant angle $(\theta \text{ or } 90 - \theta)$ in a triangle with $d$ and $A$ (must now be working with vertical distance of C of M from $A$ ) Dependent on first M
	$\alpha^{\circ} = \tan^{-1} \frac{7}{24} - \theta^{\circ}$	DM1	Dependent on the previous M1. Complete method for the required angle
	$\alpha = 2.2$	A1 [7] (11)	2.2 or better (2.22)

7a	Horizontal distance	M1	Correct use of <i>suvat</i>
,	$x = u \cos \alpha t$	A1	Correct equation
	Vertical distance	M1	Correct use of <i>suvat</i>
	$y = u \sin \alpha t - \frac{1}{2}gt^2$	A1	Correct equation. Correct signs. Condone if not using "y"
	$t = \frac{x}{u \cos \alpha} \Rightarrow$ $y = u \sin \alpha \cdot \frac{x}{u \cos \alpha} - \frac{g}{2} \left( \frac{x}{u \cos \alpha} \right)^{2}$ $\left( = x \tan \alpha - \frac{gx^{2}}{2u^{2}} \sec^{2} \alpha \right)$	DM1	Dependent on the first 2 M marks. Substitute for $t$ to obtain $y$ in terms of $x$ and $\alpha$
	$y = x \tan \alpha - \frac{gx^2}{2u^2} (1 + \tan^2 \alpha)  *$	A1*	Obtain <b>given answer</b> from correct working (final step needs to be explained).  Allow if $\sec^2 \alpha$ seen.  Must be "y" here
		[6]	
7b	$u = 20, x = 10, y > 2 \implies$ $2 = 10 \tan \theta - \frac{100g}{800} \left( 1 + \tan^2 \theta \right)$ $\left( \frac{g}{8} \tan^2 \theta - 10 \tan \theta + \left( 2 + \frac{g}{8} \right) = 0 \right)$	M1	Use given values to form quadratic in $\tan \theta$ or equivalent equation in one trig function. Allow working with =, < or > 2
	Critical values: $\theta^{\circ} = 18.6^{\circ}$ or $\theta^{\circ} = 82.7^{\circ}$	A1	One correct value to 2 sf or better
	Range: $18.6 < \theta < 82.7$	A1	Accept < or $\leq$ $(19 \leq \theta \leq 82 \text{ or } 83) \text{ max } 3 \text{ sf}$
		[3]	
7c	$y = 10 \tan 40^{\circ} - \frac{9.8 \times 100}{2 \times 400} (1 + \tan^2 40^{\circ})$	M1	Use given formula to find vertical height
	y = 6.3(03) (m)	A1	Can be implied by correctly substituted formula
	Conservation of energy	DM1	Dependent on the first M1. Need all 3 terms. Dimensionally correct. Condone sign errors.
	$\frac{1}{2}mv^{2} = \frac{1}{2}m \times 400 - mgy$ $v = 17  (16.6) (m s^{-1})$	A1ft	Correct unsimplified equation in <i>y</i> or their <i>y</i>
	$v = 17  (16.6) (m s^{-1})$	A1	2sf or 3sf only
		[5]	
7c alt	$20\cos 40^{\circ} t = 10 , t = \frac{1}{2\cos 40^{\circ}} = 0.653$ $v_V = 20\sin 40^{\circ} - gt$	M1	Complete method using <i>suvat</i> to vertical component of speed e.g. by finding time taken then use of $v = u - gt$ or finding vertical distance and using <i>suvat</i>
	= 6.5 (6.459)	A1	6.5 or better (not final answer so allow > 3sf or a correct unsimplified expression)
	$v^2 = \left(v_H\right)^2 + \left(v_V\right)^2$	DM1	Correct use of Pythagoras

			D 1
			Dependent on preceding M mark
	$\leftrightarrow v_H = 20\cos 40^\circ (=15.3)$	A1	Horizontal component of speed
	$(7V_H - 2000340 (-13.3)$	Al	seen or implied
	$v = 17  (16.6) (m s^{-1})$	A1	2sf or 3sf only
		[5]	
7d	$0 = x \tan 40^{\circ} - \frac{9.8x^{2}}{800} \left( 1 + \tan^{2} 40^{\circ} \right)$	M1	Complete method to solve for <i>x</i> .
	x = 40 (40.2) (m)	A1	2sf or 3sf only
		[2]	
7d Alt1	$y = 0 \Rightarrow t = \frac{40\sin 40^{\circ}}{g} (= 2.623)$ $x = 20\cos 40^{\circ} \times t$	M1	Complete method to solve for <i>x</i> .
	x = 40 (40.2) (m)	A1	2sf or 3sf only
		[2]	
7d Alt2	Range = $\frac{20^2 \sin 80^\circ}{g}$ = $40 (40.2) (m)$	M1	Complete method to solve for <i>x</i> .
	=40(40.2)(m)	A1	2sf or 3sf only
		[2]	
		(16)	