



Mark Scheme (Results)

October 2019

Pearson Edexcel International Advanced Level
In Physics (WPH11) Paper 01
Mechanics and Materials

Question Number	Answer	Mark
1	<p>A is the correct answer</p> <p>B is not correct as both the micro and centi columns are incorrect. C is not correct as the micro column is incorrect. D is not correct as the centi column is incorrect.</p>	(1)
2	<p>B is the correct answer</p> <p>A is not correct as they are the units for force. C is not correct as they are the units for momentum. D is not correct as they are the units for power.</p>	(1)
3	<p>C is the correct answer</p> <p>A is not correct as diameter is being used for radius. B is not correct as diameter is being used for radius. D is not correct as the anomalous point (1.36) has not been ignored.</p>	(1)
4	<p>D is the correct answer</p> <p>This is because the area under a stress-strain graph is the work done per unit volume, but the area under the other 3 graphs represents work done.</p>	(1)
5	<p>B is the correct answer</p> <p>This is because the horizontal component is calculated using the equation $v_H = \sqrt{v^2 - v_V^2} = \sqrt{0.5^2 - 0.3^2} = 0.4$</p>	(1)
6	<p>C is the correct answer</p> <p>This is because W_c should have been drawn in the centre of the cube.</p>	(1)
7	<p>C is the correct answer</p> <p>A is not correct as it ignores the weight of the table. B is a correct equation since $R_c = W_c$, but it is not an instance of the third law. D is a correct equation but it is not an instance of the third law.</p>	(1)
8	<p>C is the correct answer</p> <p>This is because the power needed is equal to the gravitational energy supplied per second (mgh) plus the kinetic energy given to the water per second ($\frac{1}{2}mv^2$).</p>	(1)
9	<p>C is the correct answer</p> <p>This is because $s = \frac{1}{2}gt^2$. So if in one unit of time the sphere has fallen one unit of distance, i.e. from image 1 to image 2, then in 2 units of time it will have fallen 4 units of distance, i.e. from image 1 to R.</p>	(1)
10	<p>B is the correct answer</p> <p>This is because the force is given by $F = kx$. So if k is doubled but x remains the same, F will be doubled.</p>	(1)

Question Number	Answer	Mark
11	<p>Horizontal force/component = $F\cos\theta$ (1)</p> <p>Work done = $F_H \times s$ Or Work done = $F \cos\theta \times s$ (1)</p> <p>As θ increases, $\cos\theta / F_H / F\cos\theta$ decreases so work done decreases. Or As θ decreases, $\cos\theta / F_H / F\cos\theta$ increases so work done increases. (1)</p>	(3)
	Total for question 11	3



Question Number	Answer	Mark
12(a)	<p>Use of $(\Delta)E_{\text{grav}} = Fd$ (1)</p> <p>Or Use of $E_k = (\Delta)E_{\text{grav}}$ AND Use of $v^2 = u^2 + 2as$ with $a = -\frac{F}{m}$ (1)</p> <p>Gradient = $\frac{mg}{F}$ Or $\frac{d}{h} = \frac{mg}{F}$ (1)</p> <p><u>Example of calculation</u></p> <p>$mgh = Fd$</p> <p>$\frac{d}{h} = \frac{mg}{F}$</p>	(2)
12(b)	<p>$u = \sqrt{2gh}$ (1)</p> <p>(Do not allow if suvat used with $a=g$)</p> <p>Use of $p = mv$ (1)</p> <p>$m_1u = (m_1 + m_2)v$ (either seen or used)</p> <p>(Do not allow if there is an m_2u term unless $u=0$) (1)</p> <p>Some working leading to the correct expression AND statement that the student is correct. (1)</p> <p><u>Example of calculation</u></p> <p>$mgh = \frac{1}{2}mv^2$</p> <p>$v = \sqrt{2gh}$</p> <p>$m\sqrt{2gh} = 2mv$</p> <p>$v = \frac{\sqrt{2gh}}{2} = \sqrt{\frac{gh}{2}}$</p>	(4)
	Total for question 12	6

Question Number	Answer	Mark
13(a)	<p>Method 1 – Calculate the vertical displacement at 102 m. See ($u_v =$) $33\sin 28^\circ$ Or 15 to 16 (m s^{-1}) Or ($u_h =$) $33\cos 28^\circ$ Or 29 (m s^{-1}) (1)</p> <p>Use of $v = s/t$ with $s = 102$ m for the time of flight needed Or Use of $v = s/t$ with $s = 10$ m for the extra time of flight needed (1)</p> <p>Use of equation(s) to determine the vertical displacement at the time calculated (1)</p> <p>Vertical displacement = $(-)$ 5.8 to 6.0 m (1)</p> <p>Comparison with required height AND height is insufficient (1) (Allow correct conclusion based on the calculated height)</p> <p>Method 2 – Calculate the horizontal displacement for a height of 4.5 m. See ($u_v =$) $33\sin 28^\circ$ Or 15 to 16 (m s^{-1}) Or ($u_h =$) $33\cos 28^\circ$ Or 29 (m s^{-1}) (1)</p> <p>Use of vertical equation(s) with $s = (-)4.5$ m to determine the actual time of flight Or to determine the time beyond 92 m (1)</p> <p>Use of $v = s/t$ to determine the range Or Use of $v = s/t$ for the extra displacement beyond 92 m (1)</p> <p>Horizontal displacement = 98 to 101 m Or extra displacement = 7.7 to 7.9 m (1)</p> <p>Comparison with required displacement AND height is insufficient Or Comparison of extra displacement AND height is insufficient (1) (Allow correct conclusion based on the calculated distance)</p> <p>Method 3 – Calculate the actual time of flight and that needed for 102 m See ($u_v =$) $33\sin 28^\circ$ Or 15 to 16 (m s^{-1}) Or ($u_h =$) $33\cos 28^\circ$ Or 29 (m s^{-1}) (1)</p> <p>Use of $v = s/t$ with $s = 102$ m for the time of flight needed (1)</p> <p>Use of vertical equation(s) to determine the actual time of flight (1)</p> <p>Time of flight needed = 3.5 s AND actual time of flight = 3.4 s (1) (5)</p> <p>Time needed > actual time AND height is insufficient (1) (Allow correct conclusion based on the calculated times)</p> <p>Example of calculation $u_v = (33\text{ m s}^{-1}) \sin 28^\circ = 15.5 \text{ m s}^{-1}$ $u_h = (33 \text{ m s}^{-1}) \cos 28^\circ = 29.1 \text{ m s}^{-1}$ $t = \frac{102 \text{ m}}{29.1 \text{ m s}^{-1}}$ $t = 3.50 \text{ s}$ $s = (15.5 \text{ m s}^{-1} \times 3.50 \text{ s}) + (\frac{1}{2} \times (-9.81 \text{ N kg}^{-1}) \times (3.50 \text{ s})^2)$ $s = -5.87 \text{ m}$</p>	

*13(b)	<p>This question assesses a student’s ability to show a coherent and logically structured answer with linkages and fully-sustained reasoning. Marks are awarded for indicative content and for how the answer is structured and shows lines of reasoning. The following table shows how the marks should be awarded for indicative content and lines of reasoning.</p> <table><tr><th>IC points</th><th>IC mark</th><th>Max linkage mark available</th><th>Max final mark</th></tr><tr><td>6</td><td>4</td><td>2</td><td>6</td></tr><tr><td>5</td><td>3</td><td>2</td><td>5</td></tr><tr><td>4</td><td>3</td><td>1</td><td>4</td></tr><tr><td>3</td><td>2</td><td>1</td><td>3</td></tr><tr><td>2</td><td>2</td><td>0</td><td>2</td></tr><tr><td>1</td><td>1</td><td>0</td><td>1</td></tr><tr><td>0</td><td>0</td><td>0</td><td>0</td></tr></table> <table><tr><td></td><td>Number of marks awarded for structure of answer and sustained line of reasoning</td></tr><tr><td>Answer shows a coherent and logical structure with linkages and fully sustained lines of reasoning demonstrated throughout</td><td>2</td></tr><tr><td>Answer is partially structured with some linkages and lines of reasoning</td><td>1</td></tr><tr><td>Answer has no linkages between points and is unstructured</td><td>0</td></tr></table> <p>Indicative content With air resistance: Vertical motion</p> <ul style="list-style-type: none">When moving up weight and (vertical component of) air resistance are acting. Or When moving up air resistance increases the resultant force.(When moving up,) downwards/vertical acceleration/deceleration increases Or upward velocity decreases more quickly.(So maximum) height is lower. <p>Horizontal motion</p> <ul style="list-style-type: none">There is a horizontal deceleration/force (due to air resistance).(So the average) horizontal velocity is lower.The (ball travels a) shorter (total) distance.	IC points	IC mark	Max linkage mark available	Max final mark	6	4	2	6	5	3	2	5	4	3	1	4	3	2	1	3	2	2	0	2	1	1	0	1	0	0	0	0		Number of marks awarded for structure of answer and sustained line of reasoning	Answer shows a coherent and logical structure with linkages and fully sustained lines of reasoning demonstrated throughout	2	Answer is partially structured with some linkages and lines of reasoning	1	Answer has no linkages between points and is unstructured	0	(6)
IC points	IC mark	Max linkage mark available	Max final mark																																							
6	4	2	6																																							
5	3	2	5																																							
4	3	1	4																																							
3	2	1	3																																							
2	2	0	2																																							
1	1	0	1																																							
0	0	0	0																																							
	Number of marks awarded for structure of answer and sustained line of reasoning																																									
Answer shows a coherent and logical structure with linkages and fully sustained lines of reasoning demonstrated throughout	2																																									
Answer is partially structured with some linkages and lines of reasoning	1																																									
Answer has no linkages between points and is unstructured	0																																									
Total for question 13		11																																								

Question Number	Answer	Mark
14(a)(i)	<p>(This moment) causes an anti-clockwise rotation/motion (about G) Or This moment is anti-clockwise (about G) (1)</p> <p>Returning/maintaining the boat to/in an upright/initial position Or Reducing the tilt of the boat Or opposing/balancing the moment caused by the wind (1)</p>	(2)
14(a)(ii)	<p>The distance d is reduced Or W/G moves to the right of U/X (1)</p> <p>The (anti-clockwise) moment is reduced Or The moment becomes/is clockwise (1)</p> <p>The boat would be less stable Or The boat will tilt further Or The boat could turn over (1)</p>	(3)
14(b)(i)	<p>When filled with water/ballast, the weight/mass (of the boat) increases (1)</p> <p>Upthrust equals the weight (of the boat) (because the boat is floating) Or Upthrust increases (because the boat is floating) (1)</p> <p>Boat moves downwards in the water Or The volume/amount of displaced water increases (1)</p> <p>Centre of gravity of displaced water is lower (1)</p>	(4)
14(b)(ii)	<p>Greater (surface) area of boat in contact with water Or greater cross-sectional area in water (in direction of travel) (1)</p> <p>There a greater resistance/drag/friction (on the boat). (1)</p> <p>(ignore references to greater risk of flooding)</p>	(2)
Total for question 14		11

Question Number	Answer	Mark
15(a)(i)	<p>Place two or more rubber bands or markers (on the cylinder) (accept markers correctly placed and labelled on diagram) (1)</p> <p>The top band should be far enough below the surface for terminal velocity to have been reached Or have more than 2 markers and check velocity is constant. (1)</p> <p>Measure time for the sphere to fall a given distance (using the stopwatch) and measure distance fallen (using the metre rule) (1)</p> <p>Either Reference to repeated measurements and averaging (1)</p> <p>(terminal velocity =) $\frac{\text{distance between markers}}{(\text{average}) \text{ time between markers}}$ (1)</p> <p>Or measure the times for different distances (1)</p> <p>(terminal velocity =) gradient of graph of distance against time (1)</p>	(5)
15(a)(ii)	<p>A larger sphere would have a greater (terminal) velocity (1)</p> <p>Weight is greater Or terminal velocity is proportional to r^2 Or takes more time to reach terminal velocity (1)</p> <p>The time of falling would be less (1)</p> <p>The (absolute) uncertainty in the time is the same Or Resolution of the stopwatch is the same Or Reaction time is the same (or they are a greater proportion of the (measured) time) (1)</p>	(4)

15(b) (i)	<p>Upthrust/U up (1)</p> <p>Drag/friction/D up (1)</p> <p>Weight/W/mg down (1)</p> <p>(-1 for each extra force over 3) (-1 if any arrow does not touch the dot) (-1 if any arrow is not close to vertical) (Accept single line up with two labelled arrow heads. Ignore the length of the arrows.)</p> <p>Examples:</p> <div style="display: flex; justify-content: space-around; align-items: center;">   </div>	(3)
15(b) (ii)	<p>Weight = (upthrust +) drag with indication that $W=3.5 \times 10^{-2}$ N (1)</p> <p>Use of upthrust = $\rho_1 V g$ (1)</p> <p>Use of drag = $6\pi r \eta v$ (1)</p> <p>$\eta = 2.1$ (Pa s) (1)</p> <p><u>Example of calculation</u></p> <p>$V = \frac{4}{3}\pi(4.8 \times 10^{-3} \text{ m})^3 = 4.63 \times 10^{-7} \text{ m}^3$</p> <p>Upthrust = $1.1 \times 10^3 \text{ kg m}^{-3} \times 4.63 \times 10^{-7} \text{ m}^3 \times 9.81 \text{ N kg}^{-1} = 5.00 \times 10^{-3} \text{ N}$</p> <p>$3.5 \times 10^{-2} \text{ N} = 5.0 \times 10^{-3} \text{ N} + 6\pi(4.8 \times 10^{-3} \text{ m} \times \eta \times 0.160 \text{ m s}^{-1})$</p> <p>$\eta = 2.07 \text{ Pa s}$</p>	(4)
Total for question 15		16

Question Number	Answer	Mark
16(a)	<p>Compares ≈ 40 (MPa) (compression) with ≈ 10 (MPa) (tension) (1)</p> <p>Breaking/fracture/ultimate stress/force (much) greater under compression Or Breaking/fracture/ultimate stress is 40 MPa under compression, and 10 MPa under tension. Or Breaking/fracture/ultimate stress is 30 MPa greater under compression. (1) (2)</p> <p>(If no other mark scored, allow 1 mark for greater energy absorbed/stored under compression)</p>	
16(b)	<p>Breaking stress = 5.00 to 5.10 ($\times 10^8$ Pa) (1)</p> <p>Use of $\sigma = F/A$ (1)</p> <p>$F = 8.0/8.1 \times 10^5$ N (1) (3)</p> <p><u>Example of calculation</u> $A = \pi \times (2.25 \times 10^{-2} \text{ m})^2 = 1.59 \times 10^{-3} \text{ m}^2$ $F = 1.59 \times 10^{-3} \text{ m}^2 \times 5.05 \times 10^8 \text{ Pa} = 8.03 \times 10^5 \text{ N}$</p>	
16(c)(i)	<p>Concrete can withstand high(er) stress/force under compression (1) Or Concrete is strong(er) under compression</p> <p>The concrete remains under compression when tensile force applied. Or Applied/tensile force first has to overcome the compression Or When tensile force applied, concrete is still under compression (1)</p> <p>The steel/rods take (some of) the force/stress Or The force/stress causes deformation of the steel (1)</p> <p>Steel can withstand a large(r) tensile force/stress Or Steel is strong(er) under tension Or Ultimate tensile stress of steel is large(r) (1) (4)</p>	
16(c)(ii)	<p>(When force removed) the rod will not return to its original length/shape Or The rod will be permanently/plastically deformed (1)</p> <p>the concrete will not compress (as much) Or The compression force will be less/zero (1) (2)</p>	
	Total for question 16	11

Question Number	Answer	Mark
17(a)(i)	The graph is less steep Or The gradient is smaller	(1) (1)
17(a)(ii)	Use of $a = \frac{v-u}{t}$ Or Use of $a = \text{gradient}$ $a_2 = 0.96 \text{ to } 1.3 \text{ m s}^{-2}$ <u>Example of calculation</u> $a_2 = \frac{13.2 \text{ m s}^{-1} - 6.8 \text{ m s}^{-1}}{(10.5 - 4)\text{s}} = 0.98 \text{ m s}^{-2}$	(1) (1) (2)
17(a)(iii)	Velocity is large(r) (in higher gears) so force (of the engine) will be smaller.	(1) (1) (2)
17(b)(i)	Conversion of mph to m s^{-1} Use of acceleration values for first and second gears only. Use of $a = \frac{v-u}{t}$ to determine a time total time = 13.0 to 14.0 s <u>Example of calculation</u> Velocity conversion = $\frac{60 \text{ mph} \times 1600 \text{ m}}{3600} = 26.7 \text{ m s}^{-1}$ $2.9 \text{ m s}^{-2} = \frac{18 \text{ m s}^{-1} - 0}{t_1} \quad t_1 = 6.21 \text{ s}$ $1.2 \text{ m s}^{-2} = \frac{26.7 \text{ m s}^{-1} - 18 \text{ m s}^{-1}}{t} \quad t_2 = 7.22 \text{ s}$ Total time = $6.21 \text{ s} + 7.22 \text{ s} = 13.4 \text{ s}$	(1) (1) (1) (1) (4)
17(b)(ii)	As velocity increases the air resistance increases (When) frictional forces are equal to the (driving) force of engine/car There is no resultant/net/unbalanced force and no acceleration	(1) (1) (1) (3)
Total for question 17		12