



Mark Scheme (Results)

October 2022

Pearson Edexcel International Advanced
Subsidiary Level in Physics (WPH12)
Paper 01 Waves and Electricity

Question Number	Answer	Mark
1	<p>D is the correct answer</p> <p>A is not the correct answer as the speed of a wave is independent of its amplitude.</p> <p>B is not the correct answer as the speed of a wave is independent of its amplitude.</p> <p>C is not the correct answer as period and frequency are both related to time. To calculate speed, a quantity involving distance is also required.</p>	(1)
2	<p>A is the correct answer</p> <p>B is not the correct answer as this transition would result in the emission of a photon with the shortest wavelength.</p> <p>C is not the correct answer as the arrow direction indicates absorption rather than emission.</p> <p>D is not the correct answer as the arrow direction indicates absorption rather than emission.</p>	(1)
3	<p>D is the correct answer</p> <p>A is not the correct answer as increasing temperature causes an increase in current for this circuit.</p> <p>B is not the correct answer as increasing temperature causes an increase in current for this circuit.</p> <p>C is not the correct answer as increasing temperature decreases the p.d. across the thermistor, but increases the p.d. across the fixed resistor.</p>	(1)
4	<p>A is the correct answer</p> <p>B is not the correct answer as both compressions and rarefactions have zero displacement of molecules at their centre.</p> <p>C is not the correct answer as both compressions and rarefactions have zero displacement of molecules at their centre.</p> <p>D is not the correct answer as both compressions and rarefactions have zero displacement of molecules at their centre.</p>	(1)
5	<p>C is the correct answer</p> <p>A is not the correct answer as the graph on the right is that of a diode.</p> <p>B is not the correct answer as the graph in the middle is that of a filament bulb.</p> <p>D is not the correct answer as the graph on the left is that of an ohmic conductor.</p>	(1)

6	<p>B is the correct answer</p> <p>A is not the correct answer as increasing the temperature of a metal wire causes an increase in the amplitude of lattice vibrations.</p> <p>C is not the correct answer as a change in the number of conduction electrons is normally related to semiconductors.</p> <p>D is not the correct answer as a change in the number of conduction electrons is normally related to semiconductors.</p>	(1)
7	<p>A is the correct answer</p> <p>B is not the correct answer as the total charge ($1.25 \times 45 \text{ C}$) is divided by e to establish the number of electrons passing in 45 seconds.</p> <p>C is not the correct answer as the total charge ($1.25 \times 45 \text{ C}$) is divided by e to establish the number of electrons passing in 45 seconds.</p> <p>D is not the correct answer as the total charge ($1.25 \times 45 \text{ C}$) is divided by e to establish the number of electrons passing in 45 seconds.</p>	(1)
8	<p>A is the correct answer</p> <p>B is not the correct answer as the light reflected is polarised.</p> <p>C is not the correct answer as some of the light is reflected.</p> <p>D is not the correct answer as the rest of the light is refracted.</p>	(1)
9	<p>B is the correct answer</p> <p>A is not the correct answer as the number of pulses detected is not related to the amount of interference that takes place.</p> <p>C is not the correct answer as the number of pulses detected is not related to the frequency of the waves.</p> <p>D is not the correct answer as the number of pulses detected is not related to the wavelength of the waves.</p>	(1)
10	<p>C is the correct answer</p> <p>A is not the correct answer as these are units of charge.</p> <p>B is not the correct answer as these are units of power.</p> <p>D is not the correct answer as these are units of the Planck constant, which is not equivalent to a volt.</p>	(1)

Question Number	Answer	Mark
11	(The pattern shows that) diffraction is taking place (1)	3
	(The pattern shows that) interference/superposition is taking place (1)	
	Bright/Maxima related to Constructive (interference) (1)	
	Or Dark/Minima related to Destructive (interference) (1)	
	Total for question 11	3

Question Number	Answer	Mark
12a	Ammeter in series with cell and an external component with resistance (1)	3
	Voltmeter parallel with cell (1)	
	Variable resistor included in circuit (1)	
12b	(Uses conservation of energy to) obtain the equation $\varepsilon = V + Ir$ (1)	4
	Compares $\varepsilon = V + Ir$ with $y = mx + c$ (1)	
	e.m.f. is the y-intercept of the graph (1)	
	Internal resistance is the negative of the gradient (1)	
	Total for question 12	7

Question Number	Answer	Mark
13a	<p>Use of $R = V/I$ (to find resistance of whole circuit) (1)</p> <p>Subtracts $9\ \Omega$ from $11\ \Omega$ (to get $2\ \Omega$) (1)</p> <p>Use of resistors in parallel formula (1)</p> <p>$R = 6.0\ \Omega$ (1)</p> <p>(MP3 - Allow $2 = \frac{3R}{3+R}$)</p> <p>OR</p> <p>Use of $R = V/I$ (to find V across $9.0\ \Omega$ resistor) (1)</p> <p>Subtracts 1.26V from 1.54V (to get 0.28V) (1)</p> <p>Conservation of charge used to establish current in R (0.0467 A) (1)</p> <p>$R = 6.0\ \Omega$ (1)</p> <p><u>Example of calculation</u></p> <p>$R = V/I$ for whole circuit = $1.54\text{ V} / 0.14\text{ A} = 11\ \Omega$</p> <p>Resistance of parallel section = $11\ \Omega - 9\ \Omega = 2\ \Omega$</p> <p>$\frac{1}{R_p} = \frac{1}{R_1} + \frac{1}{R_2}$, so $\frac{1}{R} = \frac{1}{2} - \frac{1}{3} = \frac{1}{6}$</p> <p>So $R = 6\ \Omega$</p> <p>OR</p> <p>$V = IR$ for $9.0\ \Omega$ resistor = $0.14\text{ A} \times 9.0\ \Omega = 1.26\text{ V}$</p> <p>p.d. across $3.0\ \Omega$ resistor and resistor $R = 1.54\text{ V} - 1.26\text{ V} = 0.28\text{ V}$</p> <p>(for $3.0\ \Omega$ resistor) $I = V/R = 0.28\text{ V} / 3.0\ \Omega = 0.0933\text{ A}$</p> <p>Current in resistor $R = 0.14\text{ A} - 0.0933\text{ A} = 0.0467\text{ A}$</p> <p>$R = V/I = 0.28\text{ V} / 0.0467\text{ A} = 6.0\ \Omega$</p>	4

13bi	<p>Use of cross-sectional area = πr^2 (1) Cross-sectional area = $1.8 \times 10^{-8} \text{ (m}^2\text{)}$ (1)</p> <p>(“Show that” so units not required) (MP1 – not awarded if diameter is used)</p> <p><u>Example of calculation</u> cross-sectional area = $\pi r^2 = \pi \left(\frac{0.15 \times 10^{-3} \text{ m}}{2}\right)^2 = 1.77 \times 10^{-8} \text{ m}^2$</p>	2
13bii	<p>Use of $R = \rho l/A$ (1) Length of copper wire = 9.5 m (1)</p> <p>(e.c.f. from (b)(i)) (Answer using “show that” value = 10.7 m)</p> <p><u>Example of calculation</u> $l = \frac{RA}{\rho} = \frac{(9.0 \Omega)(1.77 \times 10^{-8} \text{ m}^2)}{(1.68 \times 10^{-8} \Omega \text{ m})} = 9.48 \text{ m}$</p>	2
13biii	<p>Use of $I = nqvA$ (1) $v = 5.8 \times 10^{-4} \text{ m s}^{-1}$ (1)</p> <p>(e.c.f. from b(i)) (Answer using “show that” value = $5.2 \times 10^{-4} \text{ m s}^{-1}$) (ignore minus sign on answer)</p> <p><u>Example of calculation</u> $v = \frac{I}{nqA} = \frac{(0.14 \text{ A})}{(8.49 \times 10^{28} \text{ m}^{-3})(1.60 \times 10^{-19} \text{ C})(1.77 \times 10^{-8} \text{ m}^2)} = 5.8 \times 10^{-4} \text{ m s}^{-1}$</p>	2
Total for question 13		10

Question Number	Answer	Mark
14a	<p>The electron only receives energy from one photon Or there is a one to one interaction between photons and electrons (1)</p> <p>Some of the photon energy is needed to overcome the work function Or There is a minimum energy required to release electrons from the (surface of the) plate (1)</p> <p>Remaining photon energy is transferred to kinetic energy of electron (and is therefore lower than photon energy) Or Photon energy is shared between the work function and kinetic energy of electron (so kinetic energy less than photon energy) (1)</p>	3
14b	<p>Use of $E_k = \frac{1}{2}mv^2$ (1) Use of $hf = \Phi + \frac{1}{2}mv^2_{\text{max}}$ (1) Conversion of work function from eV into J (1) $f = 1.1 \times 10^{15}$ (Hz), so source A (1)</p> <p><u>Example of calculation</u> $E_k = \frac{1}{2}mv^2 = \frac{1}{2} \times 9.11 \times 10^{-31} \text{ kg} \times (5.70 \times 10^5 \text{ m s}^{-1})^2 = 1.48 \times 10^{-19} \text{ J}$ $\Phi = 3.68 \text{ eV} \times 1.60 \times 10^{-19} \text{ J eV}^{-1} = 5.89 \times 10^{-19} \text{ J}$ $hf = 1.48 \times 10^{-19} \text{ J} + 5.89 \times 10^{-19} \text{ J} = 7.37 \times 10^{-19} \text{ J}$ $f = \frac{7.37 \times 10^{-19} \text{ J}}{6.63 \times 10^{-34} \text{ Js}} = 1.11 \times 10^{15} \text{ Hz, so source A}$</p>	4
Total for question 14		7

Question Number	Answer	Mark
15ai	Divides 2Hz by 880 or 881Hz or 882Hz (1)	2
	0.23% / 0.2% is less than 0.3% (so heard as same frequency) (1)	
	OR	
	Calculates 0.3% of 880 Hz or 882Hz (1)	
	879.4 Hz is less than 880 Hz (so heard as same frequency) Or 882.6 Hz is greater than 882 Hz (so heard as same frequency) Or 2.6 Hz is greater than 2 Hz (so heard as the same frequency) (1)	
	<u>Example of calculation</u> $\frac{(882-880) \text{ Hz}}{882 \text{ Hz}} \times 100 = 0.23\%$	

*15aii

This question assesses a student’s ability to show a coherent and logically structured answer with linkages and fully-sustained reasoning. Marks are awarded for indicative content and for how the answer is structured and shows lines of reasoning. The following table shows how the marks should be awarded for indicative content.

IC points	IC mark	Max linkage mark	Max final mark
6	4	2	6
5	3	2	5
4	3	1	4
3	2	1	3
2	2	0	2
1	1	0	1
0	0	0	0

The following table shows how the marks should be awarded for structure and lines of reasoning.

	Number of marks awarded for structure of answer and sustained line of reasoning
Answer shows a coherent and logical structure with linkages and fully sustained lines of reasoning demonstrated throughout	2
Answer is partially structured with some linkages and lines of reasoning	1
Answer has no linkages between points and is unstructured	0

Indicative content

- The two sound waves are not coherent (as they have a different frequency)
- As they do not have a constant phase relationship/difference
Or the phase difference changes
- Loud sounds related to constructive interference/superposition
- Quiet sounds related to destructive interference/superposition
- Constructive/loud sounds when in phase
- Destructive/quiet sounds when out of phase

(IC5 – allow phase difference of $2n\pi$ radians / 0°)
 (IC6 – allow antiphase or phase difference of π radians / 180°)
 (Do not accept answers in terms of path differences or λ)

6

15b	<p>Use of $v = f\lambda$ (1)</p> <p>$\lambda = 2L$ used (1)</p> <p>Use of $v = \sqrt{\frac{T}{\mu}}$ (1)</p> <p>Decrease in tension = 2.5 N (1)</p> <p><u>Example of calculation</u></p> <p>$(f\lambda)^2 = T/\mu$</p> <p>$\lambda = 2L = 2 \times 0.187 = 0.374 \text{ m}$</p> <p>for 882 Hz, $(882 \text{ Hz} \times 0.374 \text{ m})^2 = T / 5.08 \times 10^{-3} \text{ kg m}^{-1}$</p> <p>$T = 552.8 \text{ N}$</p> <p>for 880 Hz, $(880 \text{ Hz} \times 0.374 \text{ m})^2 = T / 5.08 \times 10^{-3} \text{ kg m}^{-1}$</p> <p>$T = 550.3 \text{ N}$</p> <p>decrease in $T = 2.5 \text{ N}$</p>	4
	Total for question 15	12

Question Number	Answer	Mark
16ai	<p>Use of $n_1 \sin \theta_1 = n_2 \sin \theta_2$ (1) with $\sin \theta_2$ as 1 (1) critical angle = 75.1° (1)</p> <p>Or calculates ratio $n_2:n_1$ (1) Use of $\sin C = 1/n$ (1) critical angle = 75.1° (1)</p> <p><u>Example of calculation</u> $n_1 \sin \theta_1 = n_2 \sin \theta_2$ $1.48 \times \sin C = 1.43 \times \sin 90^\circ$ $C = 75.1^\circ$</p>	3
16aii	<p>Angle of incidence measured/stated in range $79-81^\circ$ (1) This is greater than the critical angle (1) <u>Total internal reflection</u> takes place (1)</p> <p>(MP1 can be awarded for seeing angle correctly marked on diagram) (If no angle of incidence measured, score 0) (MP3 dependent upon awarding MP2) (MP2 and MP3 can be awarded if angle of incidence is measured to be between 76° and 85°)</p> <p>(e.c.f. from (i))</p>	3
16bi	<p>Use of $n = c/v$ with $n = 1.48$ (1) Use of speed = distance / time (1) Time = 3.4×10^{-4} s (1)</p> <p>(Allow MP2 if using speed of light in a vacuum)</p> <p><u>Example of calculation</u> $v = c/n = 3.00 \times 10^8 \text{ ms}^{-1} / 1.48 = 2.03 \times 10^8 \text{ ms}^{-1}$ time = distance / speed = $70,000 \text{ m} / 2.03 \times 10^8 \text{ ms}^{-1} = 3.45 \times 10^{-4} \text{ s}$</p>	3
16bii	<p>(Lower RI leads to) lower critical angle (1)</p> <p>More light (totally internally) reflected Or less light refracted Or more of the incident light will hit the boundary at an angle greater than the critical angle (1)</p> <p>(MP2 dependent on awarding MP1)</p>	2
Total for question 16		11

Question Number	Answer	Mark
17ai	Use of $P = VI$ (1) $P = 0.11$ (W) (1) (MP1 - Allow methods where R is calculated and then either $P = I^2R$ or $P = V^2/R$ is used to calculate P) <u>Example of calculation</u> $P = VI = 12.0 \text{ V} \times 9.2 \times 10^{-3} \text{ A} = 0.11 \text{ W}$	2
17aii	Use of $E = Pt$ to calculate energy of LED (1) Use of $\nu = f\lambda$ and $E = hf$ to calculate photon energy (1) Divides total energy in one minute by energy of a photon (1) Number of photons in one minute = 2.1×10^{19} (1) (candidates who do not convert minutes into seconds can score a maximum of 2 marks – MP2 and MP3) (“show that” value leads to 1.9×10^{19}) (allow full e.c.f. from (i)) <u>Example of calculation</u> $E = Pt = 0.11 \text{ W} \times 60 \text{ s} = 6.6 \text{ J}$ $f = \frac{\nu}{\lambda} = \frac{3.00 \times 10^8 \text{ ms}^{-1}}{627 \times 10^{-9} \text{ m}} = 4.78 \times 10^{14} \text{ Hz}$ $E = hf = 6.63 \times 10^{-34} \text{ Js} \times 4.78 \times 10^{14} \text{ Hz} = 3.17 \times 10^{-19} \text{ J}$ Number of photons in one minute = $\frac{6.6 \text{ J}}{3.17 \times 10^{-19} \text{ J}} = 2.1 \times 10^{19}$	4
17b	(Lower wavelength leads to) greater (photon) energy (1) Therefore fewer photons (in one minute) (1) (MP1 – accept hc/λ increases or hf increases) (MP2 dependent on awarding of MP1)	2
17c	Use of $A = 4\pi r^2$ (1) Use of $I = P/A$ (1) $I = 2200 \text{ (W m}^{-2}\text{, which is greater than } 1100 \text{ W m}^{-2}\text{) so student is correct}$ (1) (MP2 – allow if use $A = 0.69/1100$) <u>Example of calculation</u> $A = 4\pi (0.005)^2 = 3.14 \times 10^{-4} \text{ m}^2$ $I = \frac{0.69 \text{ W}}{3.14 \times 10^{-4} \text{ m}^2} = 2196 \text{ W m}^{-2}$	3
Total for question 17		11

Question Number	Answer	Mark																																
18a	<p>Use of $n\lambda = d \sin \theta$ (1) $\theta_2 = 29^\circ$ (1)</p> <p>(For MP1, allow calculation of $d/\lambda = 4.13$ or $\lambda/d = 0.242$)</p> <p><u>Example of calculation</u> $\sin 14.0^\circ = 0.242$ (when $n = 1$) $n = \frac{d}{\lambda} \sin \theta$, so if d and λ are the same, when $n = 2$, $\sin \theta$ is doubled so $\sin \theta_2 = 0.242 \times 2 = 0.484$ $\sin^{-1} 0.484 = 28.9^\circ$</p>	2																																
18b	<p>Suitable graph suggested (see table below) (1) Calculate/determine gradient (1) Correct method for determining λ from gradient of graph (1)</p> <p>(MP2 do not award without any suggestion of the graph to be plotted) (MP2 do not award if either of the axes involves λ)</p> <table><tr><th colspan="2">MP1</th><th colspan="2">MP3</th></tr><tr><th>y-axis</th><th>x-axis</th><th>gradient =</th><th>or λ =</th></tr><tr><td>n</td><td>$d \sin \theta$</td><td>$1/\lambda$</td><td>$1/\text{gradient}$</td></tr><tr><td>$d \sin \theta$</td><td>n</td><td>λ</td><td>gradient</td></tr><tr><td>n</td><td>$\sin \theta$</td><td>d/λ</td><td>$d/\text{gradient}$</td></tr><tr><td>$\sin \theta$</td><td>n</td><td>λ/d</td><td>gradient $\times d$</td></tr><tr><td>$\sin \theta$</td><td>n/d</td><td>λ</td><td>gradient</td></tr><tr><td>n/d</td><td>$\sin \theta$</td><td>$1/\lambda$</td><td>$1/\text{gradient}$</td></tr></table>	MP1		MP3		y-axis	x-axis	gradient =	or λ =	n	$d \sin \theta$	$1/\lambda$	$1/\text{gradient}$	$d \sin \theta$	n	λ	gradient	n	$\sin \theta$	d/λ	$d/\text{gradient}$	$\sin \theta$	n	λ/d	gradient $\times d$	$\sin \theta$	n/d	λ	gradient	n/d	$\sin \theta$	$1/\lambda$	$1/\text{gradient}$	3
MP1		MP3																																
y-axis	x-axis	gradient =	or λ =																															
n	$d \sin \theta$	$1/\lambda$	$1/\text{gradient}$																															
$d \sin \theta$	n	λ	gradient																															
n	$\sin \theta$	d/λ	$d/\text{gradient}$																															
$\sin \theta$	n	λ/d	gradient $\times d$																															
$\sin \theta$	n/d	λ	gradient																															
n/d	$\sin \theta$	$1/\lambda$	$1/\text{gradient}$																															
18c	<p>Use of tan to calculate θ_2 (allow Pythagoras to find hypotenuse and then using sin or cos) (1)</p> <p>Use of $n\lambda = d\sin\theta$ with $n = 2$ (1)</p> <p>Use number of lines per m(m) = $1 / d$ (1)</p> <p>Number of lines per mm = 149, so labelling incorrect Or $d = 3.33 \times 10^{-6}$ m, not 6.69×10^{-6} m, so labelling incorrect (1)</p> <p><u>Example of calculation</u> $\tan \theta = 0.397 \text{ m} / 2.00 \text{ m} = 0.199$, $\theta = 11.2^\circ$ $n\lambda = d\sin\theta$, so $d = n\lambda / \sin \theta = 2 \times 650 \times 10^{-9} \text{ m} / \sin (11.2^\circ)$ $d = 6.69 \times 10^{-6} \text{ m}$ number of lines per metre = $1/d = 1 / 6.69 \times 10^{-6} \text{ m} = 149,000 \text{ m}^{-1}$ $= 149 \text{ mm}^{-1}$</p>	4																																
Total for question 18		9																																