



Mark Scheme (Results)

June 2024


Pearson Edexcel International Advanced
Level in Physics (WPH16) Paper 01
Practical Skills in Physics II

Question Number	Answer	Mark
1(a)	Any TWO from Connect the capacitor with the correct polarity (1) Do not exceed the working p.d. of the capacitor (1) Ensure the capacitor is fully discharged when handling (1)	2
1(b)	Clamp metre rule in position and use a set square to ensure metre rule is vertical accept spirit level (1) Ensure the metre rule is close to the mass (1) View the ruler perpendicularly Or Use a set square to read off the ruler (1)	3
1(c)(i)	Mean value of $h = 0.242$ m 3 d.p. only (1) <u>Example of calculation</u> Mean value of $h = \frac{(0.246 + 0.239 + 0.243 + 0.241)\text{m}}{4} = 0.2423 \text{ m} = 0.242 \text{ m}$	1
1(c)(ii)	Calculation of half range shown Accept furthest from mean (1) Correct percentage uncertainty given to 1 or 2 sig figs (e.c.f. 1(c)(i)) (1) <u>Example of calculation</u> Half range = $\frac{(0.246 - 0.239)\text{m}}{2} = 3.5 \times 10^{-3} \text{ (m)}$ Percentage uncertainty = $\frac{3.5 \times 10^{-3}\text{m}}{0.242\text{m}} \times 100 = 1.4\%$ Allow rounding or use of furthest from the mean to give half range of 4mm, so %U=1.7%	2
1(c)(iii)	Use of $E = \frac{1}{2}CV^2$ and $E = mgh$ (1) Use of efficiency = $\frac{\text{useful energy output}}{\text{total energy input}}$ (1) Efficiency = 0.56 Allow 56% e.c.f. 1(c)(i) (1)	3
	<u>Example of calculation</u> $E = \frac{1}{2}CV^2 = 0.5 \times (4700 \times 10^{-6})\text{C} \times (6\text{V})^2 = 0.0846 \text{ J}$ $E = mgh = (20 \times 10^{-3})\text{kg} \times 9.81\text{ms}^{-2} \times 0.242\text{m} = 0.0475 \text{ J}$ Efficiency = $\frac{0.0475\text{J}}{0.0846\text{J}} = 0.56$	
	Total for question 1	11

Question Number	Answer	Mark
2(a)	<p>Substitution of units for all variables into formula (1)</p> <p>Clear working leading to units of N s m^{-2} (1)</p> <p><u>Example of working</u></p> $\eta = \frac{\pi \rho P r^4 t}{8 L M} = \frac{(\text{kg m}^{-3})(\text{N m}^{-2})(\text{m}^4)(\text{s})}{(\text{m})(\text{kg})} = \text{N s m}^{-6} \text{m}^4 = \text{N s m}^{-2}$	2
2(b)	<ol style="list-style-type: none"> 1. Measure the internal diameter of the pipe using vernier calipers (1) 2. Repeat the measurement (of diameter) at different orientations and calculate the mean (1) 3. Ensure pipe is horizontal using a spirit level Or (Turn on the tap and wait until) pressure difference is constant Or Keep stopwatch close to the mass balance (1) 4. Measure M and corresponding value of t (1) 5. Record at least 5 sets of values. (1) 6. Plot a graph of M against t and calculate the gradient to determine η (1) <p>Accept valid alternative graphs with M and t as variables</p> <p>Accept a stated gradient if correct</p>	6
2(c)	<p>The data logger will record mass and time simultaneously (1)</p> <p>The data logger has a high sampling rate (1)</p>	2
	Total for question 2	10

Question Number	Answer	Mark
3(a)	Measure multiple oscillations and divide by the number of oscillations (1) Use a marker at the centre of the oscillation Or use a marker on the mass (1) Repeat the measurement of T and calculate a mean Or Allow the oscillations to settle before timing (1)	3
3(b)(i)	EITHER $\log T = \log a + b \log M$ (1) Compares with $y = c + mx$ where b is the gradient (which is constant) (1) MP2 dependent on MP1 OR $\log T = b \log M + \log a$ (1) Compares with $y = mx + c$ where b is the gradient (which is constant) (1) MP2 dependent on MP1	2
3(b)(ii)	Values of $\log M$ correct and consistent to 3 d.p. Allow consistent to 2 d.p. (1) Values of $\log T$ correct and consistent to 3 d.p. Allow consistent to 2 d.p. (1) Axes labelled: y as $\log (T / \text{s})$ and x as $\log (M / \text{kg})$ (1) Appropriate sensible scales chosen (1) log values plotted accurately (1) Best fit line drawn (1)	6

M / kg	T / s	$\log (M / \text{kg})$	$\log (T / \text{s})$
0.200	1.46	-0.699	0.164
0.300	1.86	-0.523	0.270
0.400	2.14	-0.398	0.330
0.500	2.36	-0.301	0.373
0.600	2.63	-0.222	0.420
0.700	2.88	-0.155	0.459



3(b)(iii)

Calculation of gradient using large triangle shown

(1)

Value of gradient in range 0.51 to 0.55

(1)

Value of gradient given to 2 or 3 s.f., positive, no unit

(1)

3

Example of calculation

$$\text{gradient} = \frac{0.485 - 0.2}{-0.1 - -0.64} = \frac{0.285}{0.54} = 0.528$$

3(b)(iv)	<p>Correct y-intercept read from graph Or Calculation of y-intercept using calculated gradient and data point from best fit line (1)</p> <p>Conversion of log value (1)</p> <p>Calculated value of a given to 2 or 3 s.f. e.c.f. (b)(iii) (1)</p> <p><u>Example of calculation</u> $\log a = y\text{-intercept} = 0.535$ $a = 10^{0.535} = 3.43$</p> <p>Allow unit of s, incorrect unit does not score MP3</p>	3
	Total for question 3	17

Question Number	Answer	Mark
4(a)(i)	<p>EITHER</p> <p>Repeat (measurements of t) at different places and calculate a mean (1)</p> <p>To reduce (the effect of) <u>random error</u> (1)</p> <p>MP2 dependent on MP1</p> <p>OR</p> <p>Check and correct for zero error (1)</p> <p>To eliminate <u>systematic error</u> (1)</p> <p>MP2 dependent on MP1</p>	2
4(a)(ii)	<p>The micrometer screw gauge has a resolution of 0.01 mm</p> <p>Or the measurement will have an uncertainty of 0.005 mm (1)</p> <p>So the percentage uncertainty is 0.35% which is small (1)</p> <p><u>Example of calculation</u></p> $\%U = \frac{0.005\text{mm}}{1.41\text{mm}} \times 100 = 0.35\%$	2
4(b)(i)	<p>Uses $V = (\text{area of semicircle} + \text{area of rectangle}) \times \text{thickness}$ (1)</p> <p>$V = 6.24 \text{ (cm}^3\text{)}$ (1)</p> <p><u>Example of calculation</u></p> $\text{Volume of semicircle} = \frac{\pi D^2 t}{8} = \frac{\pi \times (10.1\text{cm})^2 \times 0.14 \text{ cm}}{8} = 5.608 \text{ cm}^3$ $\text{Volume of rectangle} = 10.1 \text{ cm} \times 0.45 \text{ cm} \times 0.14 \text{ cm} = 0.636 \text{ cm}^3$ $V = 5.608 \text{ cm}^3 + 0.636 \text{ cm}^3 = 6.24 \text{ cm}^3$	2

4(b)(ii)	<p>EITHER</p> <p>Doubles %U in D Accept doubles $\frac{\Delta D}{D}$ (1)</p> <p>Correct calculation of %U in $\frac{\pi D^2 t}{8}$ (1)</p> <p>Or</p> <p>Correct calculation of %U in Dxt (1)</p> <p>Calculation of U in $\frac{\pi D^2 t}{8}$ and U in Dxt (1)</p> <p>U = 0.16 (cm³)</p> <p><u>Example of calculation</u></p> <p>%U in $D = 0.5\%$</p> <p>%U in $x = 2.2\%$</p> <p>%U in $t = 1.4\%$</p> <p>%U in $\frac{\pi D^2 t}{8} = (2 \times 0.5\%) + 1.4\% = 2.4\%$</p> <p>%U in $Dxt = 0.5\% + 2.2\% + 1.4\% = 4.1\%$</p> <p>U in $V = (5.61 \text{ cm}^3 \times 2.4\%) + (0.64 \text{ cm}^3 \times 4.1\%) = 0.135 \text{ cm}^3 + 0.026 \text{ cm}^3$ = 0.16 (cm³)</p> <p>OR</p> <p>Uses maximum values to calculate maximum V (1)</p> <p>Or</p> <p>Uses minimum values to calculate minimum V (1)</p> <p>Maximum $V = 6.40 \text{ (cm}^3\text{)}$ Or minimum $V = 6.08 \text{ (cm}^3\text{)}$ (1)</p> <p>Correct calculation of half range (1)</p> <p>U = 0.16 (cm³)</p> <p><u>Example of calculation</u></p> <p>Maximum $V = \frac{\pi \times (10.15 \text{ cm})^2 \times 0.142 \text{ cm}}{8} + 10.15 \text{ cm} \times 0.46 \text{ cm} \times 0.142 \text{ cm}$ = 5.74 cm³ + 0.66 cm³ = 6.40 (cm³)</p> <p>Minimum $V = \frac{\pi \times (10.05 \text{ cm})^2 \times 0.138 \text{ cm}}{8} + 10.05 \text{ cm} \times 0.44 \text{ cm} \times 0.138 \text{ cm}$ = 5.47 cm³ + 0.61 cm³ = 6.08 (cm³)</p> <p>U in $V = \frac{(6.40 - 6.08) \text{ cm}^3}{2} = 0.16 \text{ (cm}^3\text{)}$</p>	4
----------	--	---

4(c)	<p>EITHER</p> <p>Upper limit of density = 1.07 g cm^{-3} (1)</p> <p>Accepted value is larger than 1.07 g cm^{-3} the protractor may not be made of Perspex (1)</p> <p>MP2 dependent MP1</p> <p><u>Example of calculation</u></p> <p>Upper limit of density = $1.04 \text{ g cm}^{-3} \times (1 + 0.03) = 1.07 \text{ g cm}^{-3}$</p> <p>OR</p> <p>%D = 12% (1)</p> <p>As % D is greater than 3% the protractor may not be made of Perspex (1)</p> <p>MP2 dependent MP1</p>	2
	Total for question 4	12